All About Football Games

By: Jaide Snitker

Cooler Master HAF 932 Full Tower Black Case

- 6 External 5.25” Drive Bays
- 5 Internal 3.5” Drive Bays
- 7 Expansion Slots
- 4 Front USB Ports
- 1 Front Firewire Port
- 1 140mm Fan Port
- Depth 22.7”
- Width 9.0”
- Height 21.5

Asus M4N78 PRO Motherboard & AMD Athlon 64 X2 6000+ Processor

Specifications

- Processor Socket: AMD
- Manufacturer: AMD
- Processor Interface:
  - Socket AM2+
- Form Factor: ATX
- Processor Class:
  - Althon 64 X2
- Processors Supported:
  - AMD Althon
  - AMD Sempron
  - AMD Athlon x2
- Phoeniz BIOS

- Additional Technologies
- Hyper Transport
- HDCP Compliant
- Hybrid SLI Support
- Processor Speed
- X2 6000+/ 3.00 GHz
- Cores
- Dual
- L2 Cache
- 1MB
- Hyper Transport Bus
- 2600 MHz
- Bus Speed
- 1000 MHz
- Wattage
- 125W

Specifications

- Unlocked Multiplier
  - No
- Northbridge
  - NVIDIA GeForce 8300
- Memory Type
  - DDR2
- Number of Pins
  - 240-Pin
- Number of Slots
  - 4
- Maximum Memory Sup.
  - 4GB-32bit & 16GB-64bit

- Memory Supported
- 667MHz DDR2, 800MHz DDR2, 1600MHz DDR2(AM2+CPU)
- Max Memory per slot
  - 4
- Channels
  - 8
- Video Chipset
  - NVIDIA Geforce 8300
- Rending Ability
  - DirectX 10 Graphics

Specifications

- **PCI Slots-3**
- **PCI Express X1 Slots-2**
- **PCI Expresses X16-1**
- **PS/2 Keyboard Con.-1**
- **PS/2 Mouse Con.-1**
- **USB Ports-12**
- **USB Rear Panel Ports-4**
- **USB Outboard Headers-4 Expandable to 8 USB**
- **IDE Headers-1**
- **FDD Headers-1**
- **Serial ATA 3.0Gb/s Headers 6**
- **ATX Power Connectors 1-24-Pin Connector**
- **PC Power Connectors 1-4 Pin**
- **S/PDIF Connectors 1-Optical**

- **VGA Ports-1**
- **DVI Ports-1**
- **HDMI Ports-1**
- **RAID Support-Yes**
- **RAID Modes-0,0+1,1,5,JBOD**

Cooler Master Silent Pro M 850W Power Supply-ATX, Modular, 850 Watt, 80+Bronze Certified, SLI/Crossfire, 135mm Ultra Silent Fan

- **Form Factor: ATX**
- **Wattage: 850W**
- **SLI/Crossfire: SLI Certified**
- **Modular Cabling: Yes**
- **Energy Efficiency: 80 Plus Bronze**
- **Fan: 135mm**
- **Input Voltage: 90~246V,47~63Hz,+3.3:22A, +5V:22A,+12V 1:66A,+12V Rails: 1,-12 V:0.3A,+5VSB:3A**
- **Motherboard Connector: 20+4 Pin**
  - **4Pin/8-Pin EPS Connector: 2**
- **SATA Power Connector: 9**
- **Motherboard Connector: 20+4 Pin**
  - **4-Pin/8-Pin EPS Connector: 2**
  - **6-Pin/8-Pin PCI-Express Connector: 6**
  - **4-Pin Floppy Connector: 1**
  - **4-Pin Peripheral Connector: 6**
- **SATA Power Connector: 9**

Centon Dual Channel 4096MB PC6400 DDR2 800MHz Memory (2 x 2048MB)

- **Total memory size 4GB**
- **Memory Modules 2**
- **Memory Channels Dual**
- **Memory Socket Dimm**
- **Pins 240**
- **ECC NO**

Seagate 7200.12 ST3750528AS Barracuda Hard Drive - 750GB, 7200rpm, 32MB, Serial ATA-300 (OEM)

- **Drive Type**
  - **Internal**
- **Interface**
  - **Serial ATA-300**
- **Interface Type**
  - **SATA**
- **Spindle Speed**
  - **7200**
- **Buffer Memory**
  - **32 MB**
- **Form Factor**
  - **3.5”**

Creative Labs Sound Blaster Audigy SE

- On-Board Connectors
  - Line level out (Front/Side/Rear/Center/Subwoofer) or Headphone out.
  - Line In/ Microphone In/ Digital I/O Aux Audio In.

- 7.1 surround output
- 24-bit/96kHz audio solution
- 100dB signal to noise ratio
- Comprehensive Creative Media Source software provided
- EAX ADVANCED HD 3.0 support for gaming
- CMSS up-mixes stereo content to 7.1 surround

Zotac Geforce 9600 GSO Video Card- 512MB DDR3, PCI Express 2.0, DVI, HDMI, VGA

- Minimums System Requirements Vista.
- A PCI Express compliant motherboard with full-height free slot.
- installation software requires CD-ROM or DVD-ROM drive.
- Connectors: DVI, HDMI, VGA

Microsoft APB-00001 Wired Keyboard 600 - USB, Black and Keyboard Stickers.

- **Media Center**
- **Quiet-touch keys**
- **Calculator hot key**
- **Spill resistant Design**
- **Plug & Play**
- **Comfort for Either Hand**
- **Optical Technology**
- **Keyboard Sticker to shaped to fit your keyboard, transforming it to a fashion accessory.**

Diablotek INTFDDBK Internal 1.44MB Floppy Disk Drive Black.

- RDS Type: Floppy Drives
- RDS Interface: Internal
- Supported Media: 1.44MB Floppy Disks.

Lite-On iHBS112-29 12X 3D Internal Blu-Ray Writer

- Cache Size 8MB
- BD Rate 12x
- DVD Read Speed 16x
- DVD Access Time 150-200MS
- Length 6.69”
- Width 5.74”
- Height 1.62”
- Weight .65Kg
- Load Type Tray

Samsung 19” Widescreen LCD Monitor

- **Display Type**
  - **LCD**
- **Screen Size 19”**
- **Interface Type**
  - **DVI, VGA**
- **Display Colors**
  - **16.7 Million**
- **Maximum Resolution**
  - **1360x768**

Thermaltake TR2-R1/AMD Socket AM2/939/754/Aluminum/92mm Fan/CPU Cooler

• Type	CPU Fan
• Socket Type	939, 754, AMD
• Fan Speed	1300 RPM
• Noise Level	16dBA
• Air Flow	35.43 CFM
• Voltage	12 Volts
• Connector	3-Pin Motherboard
• Fan Dimenstion	92x92x38mm
• Heatsink Dimen.	102x102x46mm

Window Vista Ultimate